

support@3dcut.it

Data Sheet HIRMA PMMA

rev. 2.0 14/01/2019

SUGGESTED PRINT SETS (1)			
Suggested print sets	unit	value	test method
extruder temp	C°	220-230	internal
plate temp	C°	90-110	internal
min. nozzle diameter	mm.	0,3	internal
fan	%	0-20	internal
print speed	mm/1°	30-50	internal
PROPERTY			
Physical			
Specific gravity	g/cm3	1.17	ASTM D792
Water absorption	%	0.4	ASTM D570
Mechanical at 23°C / 50% rh			
Flexural modulus	GPa	2.3	ASTM D790
IZOD impact	J/cm	3.2	ASTM D256
Tensile strength at break	MPa	51	ASTM D638
Thermal			
Heat deflection	°C	77	ASTM D648

Disclaimer

The above information is provide in good fact .Treedfilaments is not responsable for any processing which may occur to product finished articles , packaging materials and other .

Further Treedfilaments makes no warranty or representation of any kind regarding the information given or the product described and expressly disclaims all implied warranties, representations and conditions, including without limitation all warranties and conditions of quality, merchantability and suitability or fitness for particular purpose.



Data Sheet HIRMA PMMA

rev. 2.0 14/01/2019

ADDITIONAL INFORMATIONS

In general filaments made with HIRMA (PMMA) can be processed on conventional 3D printer using FDM / FFF technology.

HIRMA (PMMA) is a dedicated polymethyl methacrylate developed for 3D printing and to obtain best results we recommend pre drying the filaments at 70° for 3 h. Increase drying time for spools up 1 kg.

Don't leave the filament stopped inside the nozzle more than 20 min. If that down the temperature under 210°, better stop the thermal control.

(1) Suggested print set merely represent a recommendation for general use . Every printer necessity a specific set , nozzle temp, bed temp, etc .

Disclaimer

The above information is provide in good fact .Treedfilaments is not responsable for any processing which may occur to product finished articles , packaging materials and other .

Further Treedfilaments makes no warranty or representation of any kind regarding the information given or the product described and expressly disclaims all implied warranties , representations and conditions , including without limitation all warranties and conditions of quality , merchantability and suitability or fitness for particular purpose .